

INDUSTRIAL COMPONENT DATA

UK 6 N GN 1003222 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 6 N GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 6 N GN
Catalog number	1003222
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-EEE3C0DF07
Generated	2026-08-04

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 41 A, connection type: Screw connection, Dimensioning cross-section: 6 mm², cross-section: 0.2 mm² - 10 mm², installation type: NS 35/7.5, NS 35/15, colour: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1003222

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626465685

Weight per Piece (excluding packing) 13.450 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of positions 1

Number of levels 1

Number of connections 2

Nominal cross section 6 mm²
Color green
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 57 A (with 10 mm² conductor cross section)
Nominal current I_N 41 A
Nominal voltage U_N 800 V
Open side panel Yes
Dimensions
Width 8.2 mm
End cover width 1.8 mm
Length 42.5 mm
Height NS 35/7,5 47 mm
Height NS 35/15 54.5 mm
Height NS 32 52 mm
Connection data
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 8
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 6 N GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.