

**INDUSTRIAL COMPONENT DATA**

# UK-SILED 24 BK 3118520 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK-SILED 24 BK



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | UK-SILED 24 BK      |
| Catalog number  | 3118520             |
| Category        | Fuse terminal block |
| Minimum order   | 50 Pcs              |
| Document ID     | EO-AD37E84A3F       |
| Generated       | 2026-08-05          |

## Product Overview

Fuse modular terminal block

Terminal block for fuse, fuse type: G/5 x 20/5 x 25, nominal voltage: 250 V, nominal current: 6.3 A, connection type: Screw connection, cross-section: 0.2 mm<sup>2</sup>- 4 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, NS 32, color: black

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3118520

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918283322

Weight per Piece (excluding packing) 18.700 g

Custom tariff number 85363010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm<sup>2</sup>

Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 1.02 W  
Fuse G / 5 x 20 / 5 x 25  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum load current 6.3 A (Determined by the fuse used.)  
Nominal current IN 6.3 A  
Nominal voltage UN 250 V (As a fuse terminal block)  
400 V (As a disconnect terminal block)  
Open side panel No  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg  
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3  
Fire protection for rail veh...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK-SILED 24 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.