

**INDUSTRIAL COMPONENT DATA**

# UKK 3-MSTB-5,08 AU 32L 2770969 PHOENIX CONTACT

## Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 3-MSTB-5,08 AU 32L



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | UKK 3-MSTB-5,08 AU 32L      |
| Catalog number  | 2770969                     |
| Category        | Feed-through terminal block |
| Minimum order   | 5 Pcs                       |
| Document ID     | EO-0C5FB584C5               |
| Generated       | 2026-08-05                  |

### Product Overview

Double-level terminal block

Double-level terminal block, 32 locked poles, nominal voltage: 250 V, nominal current: 10 A, number of connections: 128, number of poles: 32, connection type: Screw connection / plug-in connection, 1. And 2nd floor, connection on the left, cross-section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, NS 32, color: gray

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

### Additional Product Information

Key Commercial Data

Orderkey 2770969

Packing unit 5 pc

Note Made to Order (non-returnable)

GTIN 4017918243357

Weight per Piece (excluding packing) 116.400 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 128

Color gray

Insulating material PA  
Flammability rating according to UL 94 V2  
Rated surge voltage 4 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Connection method Screw connection  
Maximum load current 12 A (with 4 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 10 A  
Nominal voltage U<sub>N</sub> 250 V  
Open side panel Yes  
Dimensions  
Width 88.9 mm  
Length 50 mm  
Pitch 5.08 mm  
Height NS 35/7,5 53.5 mm  
End cover width 2.5 mm  
Connection data  
Connection method Screw connection  
Screw thread M3  
Tightening torque, min 0.5 Nm  
Tightening torque max 0.6 Nm  
Stripping length 8 mm  
Conductor cross section solid min. 0.2 mm<sup>2</sup>  
Conductor cross section solid max. 4 mm<sup>2</sup>  
Conductor cross section AWG min. 24  
Conductor cross section AWG max. 12  
Conductor cross section flexible min. 0.2 mm<sup>2</sup>  
Conductor cross section flexible max. 2.5 mm<sup>2</sup>  
Min. AWG conductor cross section, flexible 24  
Max. AWG conductor cross section, flexible 14  
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule wit...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 3-MSTB-5,08 AU 32L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.