

INDUSTRIAL COMPONENT DATA

UKK 3-MSTB-5,08-PE 1876615 PHOENIX CONTACT

Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 3-MSTB-5,08-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 3-MSTB-5,08-PE
Catalog number	1876615
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-FD21961B85
Generated	2026-08-03

Product Overview

Double-level terminal block

Double-level terminal block, number of connections: 4, number of poles: 1, connection type: Screw connection / plug-in connection, cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 1876615

Packing unit 50 pc

Catalog page Page 325 (CL-2005)

GTIN 4017918134082

Weight per Piece (excluding packing) 11.500 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Nominal current I_N 250 A

Nominal voltage U_N 1000 V

Open side panel Yes

Number of positions 1

Connection data

Connection labeling 2nd level connection left

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Connection method Screw connection

Stripping length 8 mm

Internal cylindrical gage A3

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V2

Environmental Product Compliance

REACH SVHC Lead 7439-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 3-MSTB-5,08-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.