

INDUSTRIAL COMPONENT DATA

UKK 5-HESILED 60 (5X20) 0711580 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 5-HESILED 60 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 5-HESILED 60 (5X20)
Catalog number	0711580
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-24B59C9E6A
Generated	2026-08-04

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 400 V, nominal current: 32 A, connection type: Screw connection, Sizing cross-section: 1.5 mm², cross-section: 0.2 mm²- 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20, nom. voltage: 400 V, nominal current: 32 A, connection method: Screw connection, Rated cross section: 1.5 mm², cross section: 0.2 mm²- 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Fuse terminal block

Number of connections 4

Number of rows 2

Data management status

Article revision 06

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesFuse type Glass / ceramics / ...

Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 1.02 W
Fuse G / 5 x 20
Connection data Number of connections per level 2
Nominal cross section 4 mm²
Level 1 above 1 below 1
Screw thread M3
Tightening torque 0.5 ... 0.8 Nm
Stripping length 8 mm
Internal cylindrical gage A4
Connection in acc. with standard IEC / EN
Conductor cross section rigid 0.2 mm² ... 4 mm²
Cross section AWG 24 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²
Nominal current 32 A
Maximum load current 32 A
Nominal voltage 400 V
Nominal cross section 1.5 mm²
Dimensions Width 8.2 mm
Height 86.5 mm
Depth on NS 32 84 mm
Depth on NS 35/7,5 79 mm
Depth on NS 35/15 86.5 mm
Mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 5-HESILED 60 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.