


INDUSTRIAL COMPONENT DATA

UKK 5-MTK-P/P BU 0711593 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 5-MTK-P/P BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 5-MTK-P/P BU
Catalog number	0711593
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-12CF949F90
Generated	2026-08-06

Product Overview

Knife disconnect terminal block

Blade interruptible terminal, with threaded females for test sockets to accommodate test pins, rated voltage: 400 V, rated current: 26 A, 1st and 2nd floor, connection type: Screw connection, Sizing section: 4 mm², section: 0.2 mm² - 4 mm², 2. Floor, connection type: Screw connection, Sizing section: 4 mm², Section: 0.2 mm² - 4 mm², Mounting: NS 35/7.5, NS 35/15, NS 32, Color: Blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Knife disconnect terminal block, With test socket screws for insertion of test plugs, nom. voltage: 400 V, nominal current: 26 A, connection method: Screw connection, cross section: 0.2 mm² - 4 mm², AWG: 24 - 12, length: 80 mm, width: 6.1 mm, color: blue, mounting: NS 35/7,5, NS 35/15, NS 32, nom. voltage: 400 V

Your advantages

Space-saving design just 6.2 mm wideClosed housing of double-level terminal blocksUser-friendly disconnect knife operation

Key Commercial Data

Orderkey 0711593

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918855611

Weight per Piece (excluding packing) 24.240 g

Custom tariff number 85369010

Country of origin TR (Turkey)

Dimensions

Width 6.1 mm

Length 80 mm

Height NS 35/7,5 68 mm

Height NS 35/15 75.5 mm

Height NS 32 73 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 5-MTK-P/P BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.