


INDUSTRIAL COMPONENT DATA

UM 25-PVB 2/12ICV/SO19 2298331 PHOENIX CONTACT

Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM 25-PVB 2/12ICV/SO19



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM 25-PVB 2/12ICV/SO19
Catalog number	2298331
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-D8E7D6C8D6
Generated	2026-08-05

Product Overview

Potential distributors

VARIOFACE module, with COMBICON connectors and two potentials (+ -) for potential distribution, for installation on NS 35/7.5 or NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2298331

Packing unit 1 pc

GTIN 4017918587789

Weight per Piece (excluding packing) 36.780 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 25 mm

Height 97 mm

Depth 42 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

General

Nominal voltage UN 230 V AC/DC

Total current 12 A

Mounting position any

Designation Air clearances and creepage distances

Standards/regulations DIN EN 50178: 1998-04

Rated surge voltage 2.1 kV (1.2/50 us)

Rated insulation voltage 230 V

Degree of pollution 2

Overvoltage category II

Degree of protection IP00

Connection data, supply

Number of connections 2

Connection data, distribution

Number of connections 12

Standards and Regulations

Designation Air clearances and creepage distances

Standards/regulations DIN EN 50178: 1998-04

Rated insulation voltage 230 V

Rated surge voltage 2.1 kV (1.2/50 us)

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss

7.027141152eCl@ss 8.027400609eCl@ss 9.027400609

ETIM 4.0EC001894ETIM 5.0EC001894ETIM 6.0EC002780

UNSPSC 6.0130211824UNSPSC 7.090139121421UNSPSC 1139121421UNSPSC 12.0139121421UNSPSC

13.239121432

ETIM for 2298331 Power...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM 25-PVB 2/12ICV/SO19 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.