

INDUSTRIAL COMPONENT DATA

UM-2KS50/4FLK14/YCS 2311166 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-2KS50/4FLK14/YCS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-2KS50/4FLK14/YCS
Catalog number	2311166
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-60D9F028A8
Generated	2026-08-03

Product Overview

Passive module

32-channel digital input/output module with redundant voltage power. Suitable for Yokogawa ADV 151, ADV 161, ADV 551 and ADV 561 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2311166

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356159739

Weight per Piece (excluding packing) 231.600 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Width 128 mm

Height 78 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 24 V DC $\pm 10\%$

Max. perm. current (per branch) 1 A

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method IDC/FLK pin strip

Number of connections 4

Number of positions 14

Connection data for connection 2

Connection name Controller level

Connection method Yokogawa KS-compatible

Torque 0.5 Nm

Number of connections 2

Number of positions 50

Note Usable system cables: Phoenix Contact YUC50, Yokogawa AKB331

Supported controller

Controller YOKOGAWA CS3000 CentumVP

- suitable I/O card ADV151

ADV161

ADV551

ADV561

Controller YOKOGAWA STARDOM

- suitable I/O card NFDV151

NFDV161

NFDV551

NFDV561

Standards and Regulations

Standards/regulations DIN EN 50178

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127371600eCl@ss 6.027371600eCl@ss

7.027141152eCl@ss 8.027141152eCl@ss 9.027141152

ETIM 5.0EC0027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-2KS50/4FLK14/YCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.