

INDUSTRIAL COMPONENT DATA

UM 45-PROFIL 18CM 1112627 PHOENIX CONTACT

Press-drawn section housings, Basic profile, profile width (intern..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM 45-PROFIL 18CM



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM 45-PROFIL 18CM
Catalog number	1112627
Category	Extruded profile modular housing
Minimum order	1000 Pcs
Document ID	EO-F6C677E9D5
Generated	2026-08-02

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 41.85 mm, length: 180 mm, height: 44.8 mm
 Extruded profile housings, Basic profile, profile width (inside): 41.85 mm, profile width (outside): 44.8 mm, length: 180 mm, height: 44.8 mm, depth: 18.95 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data
 Orderkey 1112627
 Packing unit 1
 GTIN 4063151033262
 Custom tariff number 39162000
 Drawings
 Dimensions
 Ambient conditions
 Standards and Regulations
 Product properties
 Material specifications

[Packaging specifications](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to top](#)[Product properties](#)

[Brief article description](#) [Profile](#)

[Type UM 45-PROFIL 18CM](#)

[Order No. 1112627](#)

[Housing type](#) [Press-drawn section housings](#)

[Type](#) [Basic profile](#)

[Back to top](#)[Dimensions](#)

[Dimensional drawing](#)

[Length](#) [180 mm](#)

[Profile width \(external\)](#) [44.8 mm](#)

[Profile width \(internal\)](#) [41.85 mm](#)

[Height](#) [44.8 mm](#)

[Depth](#) [18.95 mm](#)

[Back to top](#)[Material specifications](#)

[Housing material](#) [PVC](#)

[Back to top](#)[Ambient conditions](#)

[Ambient temperature \(operation\)](#) [-15 °C ... 50 °C](#)

[Back to top](#)[Packaging specifications](#)

[Pieces per package](#) [10](#)

[Denomination packing units](#) [Pcs.](#)

[Back to top](#)[Standards and Regulations](#)

[Flammability rating according to](#) [UL 94 V0](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 10.0.1](#) [27182701](#)

[eCl@ss 8.0](#) [27182701](#)

[eCl@ss 9.0](#) [27182701](#)

[Back to top](#)[ETIM](#)

[ETIM 5.0](#) [EC002779](#)

[Back to top](#)

[ETIM for 1112627](#) [Low-voltage industrial controls and switchgear \(EC002779\)](#)

[Feature Name](#)

[Feature Value](#)

[Type of enclosure \(EF003086\)](#)

[Closed](#)

[Housing connectable \(EF003088\)](#)

[No](#)

[Material \(EF002169\)](#)

[Other](#)

[Surface finishing \(EF006569\)](#)

[Other](#)

[Width \(EF000008\)](#)

[180 mm](#)

Height (EF000040)

44.8 mm

Depth (EF000049)

18.95 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM 45-PROFIL 18CM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.