

INDUSTRIAL COMPONENT DATA

UM 45-PROFIL 6,9CM 1105898 PHOENIX CONTACT

Press-drawn section housings, Basic profile, profile width (inter..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM 45-PROFIL 6,9CM



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM 45-PROFIL 6,9CM
Catalog number	1105898
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-4539EE3D64
Generated	2026-07-31

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 41.85 mm, length: 69 mm, height: 44.8 mm
Extruded profile boxes, Basic profile, profile width (inside): 41.85 mm, profile width (outside): 44.8 mm, length: 69 mm, height: 44.8 mm, depth: 18.95 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1105898

Packing unit 1

GTIN 4055626990743

Custom tariff number 39162000

Drawings

Dimensions

Ambient conditions

Standards and Regulations

Product properties

Material specifications

[Packaging specifications](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to top](#)[Product properties](#)

[Brief article description](#) [Profile](#)

Type UM 45-PROFIL 6,9CM

Order No. 1105898

Housing type [Press-drawn section housings](#)

Type [Basic profile](#)

[Back to top](#)[Dimensions](#)

[Dimensional drawing](#)

Length 69 mm

Profile width (external) 44.8 mm

Profile width (internal) 41.85 mm

Height 44.8 mm

Depth 18.95 mm

[Back to top](#)[Material specifications](#)

Housing material [PVC](#)

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -15 °C ... 50 °C

[Back to top](#)[Packaging specifications](#)

Pieces per package 10

Denomination packing units [Pcs.](#)

[Back to top](#)[Standards and Regulations](#)

Flammability rating according to [UL 94 V0](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 10.0.1 27182701](#)

[eCl@ss 8.0 27182701](#)

[eCl@ss 9.0 27182701](#)

[Back to top](#)[ETIM](#)

[ETIM 5.0 EC002779](#)

[Back to top](#)

[ETIM for 1105898 Low-voltage industrial controls and switchgear \(EC002779\)](#)

[Feature Name](#)

[Feature Value](#)

Type of enclosure ([EF003086](#))

[Closed](#)

Housing connectable ([EF003088](#))

[No](#)

Material ([EF002169](#))

[Other](#)

Surface finishing ([EF006569](#))

[Other](#)

Width ([EF000008](#))

[69 mm](#)

Height (EF000040)

44.8 mm

Depth (EF000049)

18.95 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM 45-PROFIL 6,9CM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.