


INDUSTRIAL COMPONENT DATA

UM-4SL/SPT/ADR541/CS 2968522 PHOENIX CONTACT

Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-4SL/SPT/ADR541/CS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-4SL/SPT/ADR541/CS
Catalog number	2968522
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-DA80FA73C0
Generated	2026-08-04

Product Overview

Passive module

Interconnect module for coupling the field side by means of a spring connection to the Yokogawa ADR 541 card. Fuse (5 x 20) with fuse fault indication (LED) per channel. AKB 334 system connection for control system.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2968522

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356340618

Weight per Piece (excluding packing) 1,015.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 232.5 mm

Height 126 mm

Depth 104 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Note Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.

Max. perm. operating voltage 24 V DC $\pm 10\%$

Max. perm. current (per branch) 630 mA

Max. permissible current (all branches) 6.3 A

Status display Green LED

Mounting position any

Assembly instructions In rows with zero spacing

Connection data for connection 1

Connection name Field level

Connection method Spring-cage connection

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Number of positions 32

Connection data for connection 2

Connection name Controller level

Connection method COMBICON connectors

Number of connections 4

Number of positions 18

Note Yokogawa AKB334-compatible

Supported controller

Controller YOKOGAWA CS3000 CentumVP

- suitable I/O card ADR541

Standards and Regulations

Standards/regulations DIN EN 50178

Rated surge voltage 0.8 kV (basic in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-4SL/SPT/ADR541/CS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.