

INDUSTRIAL COMPONENT DATA

UM-BASIC 72 L13,14CM KMGY 1017444 PHOENIX CONTACT

Press-drawn section housings, Basic profile, profile width..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-BASIC 72 L13,14CM KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-BASIC 72 L13,14CM KMGY
Catalog number	1017444
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-1822331BF3
Generated	2026-07-27

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 72 mm, length: 131.4 mm, color: light gray (7035)
 Extruded profile housings, Locking with side elements, locking with foot element, Basic profile, profile width (inside): 72 mm, length: 131.4 mm, depth: 19.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data
 Orderkey 1017444
 Packing unit 1
 GTIN 4055626511740
 Custom tariff number 39269097
 Product properties
 Material specifications
 PCB specifications
 Packaging specifications
 Dimensions
 Ambient conditions
 General information
 Classifications

Product properties[Brief article description Profile](#)[Type UM-BASIC 72 L13,14CM KMGY](#)[Order No. 1017444](#)[Housing type Press-drawn section housings](#)[Type Basic profile](#)[Mounting type Latching with side elements, latching with foot element](#)[Back to topDimensions](#)[Profile PCB width \(selectable\): 72 mm \[UM72\]](#)[Depth \[d \] 19.8 mm](#)[Back to topMaterial specifications](#)[Housing material PVC](#)[Color \(RAL\) light gray \(7035\)](#)[Flammability rating according to UL 94 V0](#)[Back to topAmbient conditions](#)[Ambient temperature \(storage/transport\) -40 °C ... 50 °C](#)[Ambient temperature \(assembly\) -5 °C ... 50 °C](#)[Ambient temperature \(operation\) -15 °C ... 50 °C \(depending on power dissipation\)](#)[Relative humidity \(storage/transport\) 95 %](#)[Back to topPCB specifications](#)[Mounting position parallel to the DIN rail](#)[Type of PCB mount Insertion/securing with additional elements](#)[Back to topGeneral information](#)[Type of note Assembly instruction:](#)[Note Refer to the data sheet for the range in the download area.](#)[Back to topPackaging specifications](#)[Pieces per package 10](#)[Denomination packing units Pcs.](#)[Back to topClassifications](#)[eCl@ss](#)[eCl@ss 10.0.1 27182701](#)[eCl@ss 8.0 27182701](#)[eCl@ss 9.0 27182701](#)[Back to topETIM](#)[ETIM 5.0 EC002779](#)[ETIM 6.0 EC002779](#)[ETIM 7.0 EC002779](#)[Back to top](#)[ETI...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-BASIC 72 L13,14CM KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.