

## INDUSTRIAL COMPONENT DATA

# UM-BASIC-KIT-B72-L150-7035 1300348 PHOENIX CONTACT

## Profile box (PVC), mounting class: DIN rail mounting, DIN..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-BASIC-KIT-B72-L150-7035



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | UM-BASIC-KIT-B72-L150-7035 |
| Catalog number  | 1300348                    |
| Category        | Electronic enclosure       |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-13A2CEDD45              |
| Generated       | 2026-08-01                 |

### Product Overview

Profile box (PVC), mounting class: DIN rail mounting, DIN rail size: width: 153.8 mm, height: 92.3 mm, depth: 39.45 mm, incl. 2 side elements (PA), colour: light grey (7035), for printed circuit boards with width: 72 mm, length: 150 mm, printed circuit board surface: 9030 mm<sup>2</sup>

Profile housing (PVC), mounting type: Rail mounting, colour: luminous grey (7035), DIN rail size: width: 153.8 mm, height: 92.3 mm, depth: 39.45 mm, incl. 2 side elements (PA), colour: luminous grey (7035), for printed circuit boards with width: 72 mm, length: 150 mm, printed circuit board area: 9030 mm<sup>2</sup>

Profile housing (PVC), mounting type: DIN rail mounting, color: light grey (7035), dimensions on the DIN rail: width: 153.8 mm, height: 92.3 mm, depth: 39.45 mm, incl. 2 lateral elements (PA), color: light grey (7035), for PCBs with width: 72 mm, length: 150 mm, PCB surface: 9030 mm<sup>2</sup>

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.

Product propertiesProduct type Stackable housing set

Type incl. 2 lateral elements

Housing type Profile housing

Housing series UM-BASIC

DimensionsWidth 153.8 mm

Height 92.3 mm

Depth 39.45 mm  
Depth from top edge of DIN rail 32.45 mm  
Dimensions 72 mm x 150 mm (PCB dimensions)  
PCB design  
PCB thickness 1.4 mm ... 1.8 mm  
Material specificationsColor light grey (7035)  
Flammability rating according to UL 94 V0  
Insulating material PVC  
Housing material PVC  
Environmental and real-life conditionsAmbient conditions  
Ambient temperature (operation) -15 °C ... 50 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 50 °C  
Ambient temperature (assembly) -5 °C ... 50 °C  
Relative humidity (storage/transport) 95 %  
PCB dataNumber of PCB holders 3  
Type of PCB mount Insertion/securing with additional elements  
Total PCB surface 9030 mm<sup>2</sup>  
Thickness of the PCB 1.4 mm ... 1.8 mm  
MountingMounting type DIN rail mounting  
Mounting position parallel to the DIN rail  
Packaging specificationsType of packaging packed in cardboard  
Outer packaging type Carton  
ETIM for 1300348 Cabinets and enclosures (EC001031)  
Feature Name  
Feature Value  
Material (EF002169)  
Other  
Colour (EF000007)  
Grey

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-BASIC-KIT-B72-L150-7035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.