

INDUSTRIAL COMPONENT DATA

UM-D25SUB/F/PTS/MSTB/GF-AI 2902087 PHOENIX CONTACT

Input module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D25SUB/F/PTS/MSTB/GF-AI



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D25SUB/F/PTS/MSTB/GF-AI
Catalog number	2902087
Category	Interface module
Minimum order	10 Pcs
Document ID	EO-F23B1FB5F7
Generated	2026-08-04

Product Overview

Input module

VARIOFACE analogue input module, with COMBICON screw connection and a 25-pole SUB D connection socket. With a knife separation, the signal track can be interrupted.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2902087

Packing unit 1

GTIN 4046356648585

Custom tariff number 85369010

Dimensions

Width 111 mm

Height 126 mm

Depth 56 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

General

Max. perm. operating voltage 25 V AC/DC

Max. perm. current (per branch) 2 A
Mounting position any
Degree of protection IP00
Connection data for connection 1
Connection name Field level
Connection method Screw connection
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB socket strip
Number of positions 25
Standards and Regulations
Designation Air clearances and creepage distances
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 50 V
Rated surge voltage 0.5 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss
7.027141152eCl@ss 8.027141152eCl@ss 9.027141152
ETIM 4.0EC002780ETIM 5.0EC002780ETIM 6.0EC002780
UNSPSC 6.0130211824UNSPSC 7.090139121421UNSPSC 1139121421UNSPSC 12.0139121421UNSPSC
13.239121432
ETIM for 2902087 PLC's (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D25SUB/F/PTS/MSTB/GF-AI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.