

INDUSTRIAL COMPONENT DATA

UM-D25SUB/F/PTS/MSTB/GF-AO 2902086 PHOENIX CONTACT

Analog VARIOFACE output module, with COMBICON screw conne..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D25SUB/F/PTS/MSTB/GF-AO



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D25SUB/F/PTS/MSTB/GF-AO
Catalog number	2902086
Category	Interface module
Minimum order	10 Pcs
Document ID	EO-C289D5726E
Generated	2026-08-04

Product Overview

Analog VARIOFACE output module, with COMBICON screw connection and a 25-pos. D-SUB female connector. The signal path can be interrupted with a disconnect knife.

VARIOFACE analogue output module, with COMBICON screw connection and a 25-pole SUB D connection socket. With a knife separation, the signal track can be interrupted.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Analog VARIOFACE output module, with COMBICON screw connection and a 25-pos. D-SUB female connector. The signal path can be interrupted with a disconnect knife.

Key Commercial Data

Orderkey 2902086

Packing unit 1

GTIN 4046356648578

Custom tariff number 85369010

Dimensions

Width 75 mm

Height 111 mm

Depth 56 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Maximum altitude ≤ 2000 m

Degree of protection IP00

General

Nominal voltage UN 25 V AC/DC

Max. perm. current (per branch) 2 A

Mounting position any

Degree of protection IP00

Connection data

Connection name Field level

Connection method Screw connection

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data 2

Connection name Controller level

Connection method D-SUB socket strip

Number of positions 25

Standards and Regulations

Designation Air clearances and creepage distances

Standards/regulations DIN EN 50178: 1998-04

Rated insulation voltage 50 V

Rated surge voltage 0.5 kV (1.2/50 us)

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0 27250313

eCl@ss 4.1 27250313

eCl@ss 5.0 27250313

eCl@ss 5.1 27250300

eCl@ss 6.0 27242600

eCl@ss 7.0 27...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D25SUB/F/PTS/MSTB/GF-AO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.