

INDUSTRIAL COMPONENT DATA

UM-D37M/DS/FU/LED/AO/C300/L 2905243 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/DS/FU/LED/AO/C300/L



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D37M/DS/FU/LED/AO/C300/L
Catalog number	2905243
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-4216C7F4F4
Generated	2026-08-06

Product Overview

Interface module

16-channel module for Honeywell C300 analog boards with separation, test points, 500 mA fuses, and fuse status indicator.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2905243

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356947091

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 85369010

Country of origin US (United States)

Dimensions

Width 104 mm

Height 142.3 mm

Depth 79 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 75 °C

General

Note Standard or halogen-free cables

Max. perm. operating voltage 24 V DC

Max. perm. current (per branch) 500 mA (fuse limited)

Max. permissible current (separate power supply) 4 A (via D-SUB)

Number of positions 37

Status display No

Mounting position any

Assembly instructions In rows with zero spacing

Connection data for connection 1

Connection name Field level

Connection method Screw connection with disconnect knife

Stripping length 8 mm

Screw thread M 3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 37

Supported controller

Controller HONEYWELL Experion PKS C300/C-Series

- suitable I/O card TAOX01 (non-redundant)

TAOX11 (redundant)

TAOX51 (non-redundant)

TAOX61 (redundant)

TAON01 (non-redundant)

TAON11 (redundant)

Controller Honeywell Experion LX Series 8

- suitable I/O card 8X-TAOXA1

8X-TAOXB1

Standards and Regulations

Standards/regulations...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/DS/FU/LED/AO/C300/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.