


INDUSTRIAL COMPONENT DATA

UM-D37M/DS/FU/LED/AO/C300/R 2905131 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/DS/FU/LED/AO/C300/R



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D37M/DS/FU/LED/AO/C300/R
Catalog number	2905131
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-E8EC602F41
Generated	2026-08-06

Product Overview

Interface module

16-channel module for Honeywell C300 analog boards with separation, test points, 500 mA fuses, and fuse status indicator.
16-channel module for Honeywell C300 analog output cards with disconnect, test points, socketed 500 mA fuses and fuse status indicator.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Interface module

Product family VARIOFACE

Number of positions 37

No. of channels 16

Data management status

Article revision 00

Electrical propertiesNominal voltage UN 24 V DC

Max. current carrying capacity per branch 500 mA (fuse limited)

Max. total current of voltage supply 4 A (via D-SUB)

Supported controller HONEYWELL Experion PKS C300/C-Series

Suitable I/O card TAOX01 (non-redundant)

TAOX11 (redundant)

TAOX51 (non-redundant)
TAOX61 (redundant)
TAON01 (non-redundant)
TAON11 (redundant)
Supported controller HONEYWELL Experion LX Series 8
Suitable I/O card 8X-TAOXA1
8X-TAOXB1
Connection dataField level
Connection method Screw connection with disconnect knife
Stripping length 8 mm
Screw thread M 3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
SignalingStatus display no
Status display present Yes, if the fuse fails
DimensionsItem dimensions
Width 104 mm
Height 142.3 mm
Depth 79 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 75 °C
Standards and regulationsStandards/regulations DIN EN 50178
MountingMounting type DIN rail mounting
Assembly note in rows with zero spacing
Mounting position any
NotesGeneral Standard or halogen-free cables....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/DS/FU/LED/AO/C300/R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.