

INDUSTRIAL COMPONENT DATA

UM-DELTA V/D/SI/BFI 5603253 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-DELTA V/D/SI/BFI

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-DELTA V/D/SI/BFI
Catalog number	5603253
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-6AEC820527
Generated	2026-08-04

Product Overview

Passive module
VARIOFACE Interconnect Module with Fuse and Fuse Fault Indication
VARIOFACE interface module with fuse and fuse failure display

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Interface module
Product family VARIOFACE
Number of positions 16
Data management status
Article revision 05
Electrical propertiesNominal voltage UN 24 V DC
Max. current carrying capacity per branch 50 mA (in as-supplied state, with one 50 mAF fuse, max. 1 A permitted)
Supported controller EMERSON DeltaV
Suitable I/O card VE4001S2T2B3
VE4001S2T2B3 Series 2
VE4001S2T1B3
VE4002S1T1B3
VE4002S1T2B3

VE4002S1T2B3 Series 2

Connection dataField level

Connection method Screw connection

Stripping length 7 mm

Conductor cross section rigid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 16

Pitch 2.54 mm

SignalingStatus display present Yes, if the fuse fails

DimensionsItem dimensions

Width 61 mm

Height 126 mm

Depth 71 mm

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Standards and regulationsStandards/regulations IEC 60664

IEC 60664A

DIN VDE 0110

DIN VDE 0160 (in parts)

MountingMounting type DIN rail mounting

Mounting position any

NotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed.
For applications or use with third-party products, the specifications, and the safety and warning instructions of the respecti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-DELTA V/D/SI/BFI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.