

INDUSTRIAL COMPONENT DATA

UM-DELTA V/A/T/SI/BFI 5603254 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-DELTA V/A/T/SI/BFI



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-DELTA V/A/T/SI/BFI
Catalog number	5603254
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-F69188D2A5
Generated	2026-08-04

Product Overview

Passive module

VARIOFACE interconnect module with blade interrupt, fuse and fuse failure indication

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 5603254

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4017918923075

Weight per Piece (excluding packing) 250.000 g

Custom tariff number 85369010

Country of origin US (United States)

Dimensions

Width 61 mm

Height 126 mm

Depth 71 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 24 V DC

Max. perm. current (per branch) 50 mA (in as-supplied state, with one 50 mA fuse, max. 1 A permitted)

Number of positions 16

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Screw connection

Stripping length 7 mm

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 16

Pitch 2.54 mm

Supported controller

Controller Emerson DeltaV

- suitable I/O card VE4003S2B4

VE4005S2B3

VE4003S3B5

Standards and Regulations

Connection in acc. with standard CUL

Standards/regulations IEC 60664

IEC 60664A

DIN VDE 0110

DIN VDE 0160 (in parts)

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-DELTA V/A/T/SI/BFI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.