

**INDUSTRIAL COMPONENT DATA**

# UM-FLK14/8RM/MSTB/GF-DO 2902084 PHOENIX CONTACT VARIOFACE relay module, with COMBICON screw connection and a..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-FLK14/8RM/MSTB/GF-DO



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | UM-FLK14/8RM/MSTB/GF-DO |
| Catalog number  | 2902084                 |
| Category        | Interface module        |
| Minimum order   | 10 Pcs                  |
| Document ID     | EO-7FD80BE129           |
| Generated       | 2026-08-04              |

## Product Overview

VARIOFACE relay module, with COMBICON screw connection and a 14-pos. flat-ribbon cable connector, 1 PDT, 8 miniature switching relays, LED, and fuse per channel

VARIOFACE relay module, with COMBICON screw connection and a plug-in connector for 14-pin flat cable, 1 inverter, 8 switching mini-relays, indicator light and fuse per channel

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

VARIOFACE relay module, with COMBICON screw connection and a 14-pos. flat-ribbon cable connector, 1 PDT, 8 miniature switching relays, LED, and fuse per channel

Key Commercial Data

Orderkey 2902084

Packing unit 1

GTIN 4046356648554

Custom tariff number 85369010

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 115 mm  
Height 126 mm  
Depth 64 mm  
Ambient conditions  
Ambient temperature (operation) -20 °C ... 50 °C  
Maximum altitude max. 2000 mm  
Degree of protection IP00  
Input data  
Nominal input voltage UN 24 V DC  
Input voltage range in reference to UN 0.8 ... 1.2  
Typical input current at UN Related to the assembly  
Type of protection Free-wheeling diode  
Protective circuit/component Polarity protection diode  
Status display/channel Yellow LED  
Output data  
Contact type 1 PDT  
Maximum switching voltage 250 V AC/DC  
Limiting continuous current 3 A  
General  
Degree of protection IP00  
Mounting position any  
Connection data  
Connection name Supply  
Connection method Screw connection  
Conductor cross section solid 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section AWG 24 ... 12  
Connection data 2  
Connection name Controller level  
Connection in acc. with standard IEC 60603-13  
Connection method Flat-ribbon cable connector in acc. with IEC 60603-13  
Number of connections 1  
Number of positions 14  
Connection data 3  
Connection name Field level  
Connection method Screw connection  
Conductor cross....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-FLK14/8RM/MSTB/GF-DO with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.