

INDUSTRIAL COMPONENT DATA

UM-KS50/32-MR/1/SI/ADV551 2901650 PHOENIX CONTACT

32-channel output relay module (1 N/O contact, optionally ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-KS50/32-MR/1/SI/ADV551



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-KS50/32-MR/1/SI/ADV551
Catalog number	2901650
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-C8A54C6095
Generated	2026-08-05

Product Overview

32-channel output relay module (1 N/O contact, optionally non-isolated) with screw connection, fuse (1 AT), and 50-pos. system connection. Suitable for the Yokogawa ADV 551 and ADV 561 cards.

32-channel output relay module (1 normally open contact, optionally linked to potential) with screw connection, fuse (1 AT) and 50-pin system connector. Suitable for Yokogawa ADV 551 and ADV 561 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

32-channel output relay module (1 N/O contact, optionally non-isolated) with screw connection, fuse (1 AT), and 50-pos. system connection. Suitable for the Yokogawa ADV 551 and ADV 561 cards.

Key Commercial Data

Orderkey 2901650

Packing unit 1

GTIN 4046356620444

Custom tariff number 85369010

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Input data

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.9 ... 1.1

Typical input current at UN 6.5 mA

Protective circuit/component Damping diode

Operating voltage display Green LED

Status display/channel Yellow LED

Output data

Contact type Single contact, 1 N/O contact

Maximum switching voltage 24 V AC/DC

Output fuse 1 A Slow-blow (TR 5)

Fuse Slow-blow (TR 5)

Connection data for connection 1

Connection name Field level

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method Yokogawa KS-compatible

Torque 0.5 Nm

Number of connections 2

Number of positions 50

Note Usable system cables: Phoenix Contact YUC50, Yokogawa AKB331

Standards and Regulations

Standards/regulations DIN EN 50178

Rated surge voltage....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-KS50/32-MR/1/SI/ADV551 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.