

INDUSTRIAL COMPONENT DATA

UM-KS50/32-MR/21/ADV151/SO207 2311111 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-KS50/32-MR/21/ADV151/SO207



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-KS50/32-MR/21/ADV151/SO207
Catalog number	2311111
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-ECA6F4E537
Generated	2026-08-03

Product Overview

Active module

32-channel input relay module with spring connection and 50-pole system connection. The excitation side is protected and optionally connected to the potential. Suitable for Yokogawa ADV 151 and ADV161 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2311111

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356145916

Weight per Piece (excluding packing) 760.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 231 mm

Height 128 mm

Depth 58 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C (95%/50°C (non-condensing))

Ambient temperature (storage/transport) -20 °C ... 70 °C

Input data

Nominal input voltage UN 24 V DC (Supply, 2 A (V1+, V2+), pluggable fuse (IEC 60127-37/IV, 2AT))

Input voltage range in reference to UN 0.8 ... 1.1

Typical input current at UN 9 mA (per channel, pluggable fuse (IEC 60127-3/IV, 1AT))

Protective circuit/component Damping diode

Type of protection Reverse polarity protection

Protective circuit/component Polarity protection diode

Operating voltage display Green LED

Status display/channel Yellow LED

Output data

Contact type 1 N/O contact

Contact material AgSnO, hard gold-plated

Maximum switching voltage < 50 V DC

Limiting continuous current 100 mA

Maximum inrush current 1 A (Supply, (P1+, P2+), pluggable fuse (IEC 60127-3/IV, 1AT))

General

No. of channels 32

Degree of protection IP00

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Spring-cage connection

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 1.5 mm²...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-KS50/32-MR/21/ADV151/SO207 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.