

INDUSTRIAL COMPONENT DATA

UM-KS50/32-MR/21/ADV551/SO207 2311108 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-KS50/32-MR/21/ADV551/SO207



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-KS50/32-MR/21/ADV551/SO207
Catalog number	2311108
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-CF5F3E415D
Generated	2026-08-05

Product Overview

Active module

32-channel output relay module (1 normally open contact, optionally linked to potential) with spring connection, fuse (2 AT) and 50-pin system connector. Suitable for Yokogawa ADV 551 and ADV 561 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2311108

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356145909

Weight per Piece (excluding packing) 871.000 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 267.5 mm

Height 127.5 mm

Depth 44 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Input data

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.9 ... 1.1

Typical input current at UN 7 mA (per channel)

Type of protection Damping diode, polarity protection

Protective circuit/component Damping diode, polarity protection diode

Operating voltage display Green LED

Status display/channel Yellow LED

Output data

Contact type 1 N/O contact

Contact material AgSnO

Maximum switching voltage 230 V AC

Limiting continuous current 2 A (Per channel, pluggable fuse (IEC 6012-3/IV, 2AT))

Maximum inrush current 8 A (Supply, (V1+, V2+), pluggable fuse (UL 248-14, 250 V, 8AT))

Min. switching current 100 mA

Interrupting rating (ohmic load) max. 48 W (at 24 V DC)

20 W (at 48 V DC)

18 W (at 60 V DC)

23 W (at 110 V DC)

40 W (at 220 V DC)

500 VA (for 250 V AC)

General

No. of channels 32

Degree of protection IP00

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Spring-cage connection

Conductor cross section solid 0.2 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-KS50/32-MR/21/ADV551/SO207 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.