

INDUSTRIAL COMPONENT DATA

UM-PRO 108 COVER/BUS-R BK 2202857 PHOENIX CONTACT

Press-drawn section housings, Lateral element (right), wid..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-PRO 108 COVER/BUS-R BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-PRO 108 COVER/BUS-R BK
Catalog number	2202857
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-24B064D61E
Generated	2026-08-03

Product Overview

Press-drawn section housings, Lateral element (right), width: 19.5 mm, color: black (9005), height: 127.8 mm
Extruded profile housings, Rail mounting/wall mounting (with optional fixing flange), Side element (right) with bus break and DIN rail mounting foot, colour: black (9005), width: 19.5 mm, height: 127.8 mm, depth: 39.45 mm
Press-drawn section housings, DIN rail mounting/wall mounting (with optional mounting flange), Side element (right) with bus breakout and with mounting foot for the DIN rail, width: 19.5 mm, height: 127.8 mm, depth: 39.45 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Panel mounting base side part

Housing type Press-drawn section housings

Housing series UM-PRO

Product family UM-PRO 108

Type Side element (right) with bus breakout and with mounting foot for the DIN rail

Data management status

Article revision 00

DimensionsWidth 19.5 mm

Height 127.8 mm

Depth 39.45 mm

Depth from top edge of DIN rail 32.45 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specifications Color (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditions Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Degree of protection (IP code)
Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
Ambient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
PCB data Type of PCB mount Insertion/securing with additional elements
Thickness of the PCB 1.4....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-PRO 108 COVER/BUS-R BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.