

INDUSTRIAL COMPONENT DATA

UM-PRO 108 L 7,40CM GY7035 BO 2203778 PHOENIX CONTACT Press-drawn section housings, Basic profile, profile w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-PRO 108 L 7,40CM GY7035 BO



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-PRO 108 L 7,40CM GY7035 BO
Catalog number	2203778
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-797537DBD8
Generated	2026-08-03

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 108 mm, length: 74 mm, color: light gray (7035)
 Extruded profile boxes, Locking with side elements, locking with floor element, Basic profile, colour: light grey (7035), profile width (inside): 108 mm, length: 74 mm, depth: 19.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2203778

Packing unit 1

GTIN 4055626431307

Custom tariff number 39169010

Product properties

Material specifications

PCB specifications

Environmental Product Compliance

Dimensions

Ambient conditions

Packaging specifications

Classifications

Product properties

Brief article description Profile

Type UM-PRO 108 L 7,40CM GY7035 BO

Order No. 2203778

Housing type Press-drawn section housings

Type Basic profile

Mounting type Latching with side elements, latching with foot element

Back to topDimensions

Length 74 mm

Profile PCB width (selectable): 108 mm [UM108]

Profile width (internal) 108 mm

Depth 19.8 mm

Back to topMaterial specifications

Housing material Polyamide

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topPCB specifications

PCB holders 3

PCB thickness 1.4 mm ... 1.8 mm

Mounting position parallel to the DIN rail

Type of PCB mount Insertion/securing with additional elements

Back to topPackaging specifications

Pieces per package 1

Denomination packing units Pcs.

Back to topEnvironmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Back to topClassifications

eCI@ss

eCI@ss 10....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-PRO 108 L 7,40CM GY7035 BO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.