

INDUSTRIAL COMPONENT DATA

UM-TM (6X10) 0830908 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-TM (6X10)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-TM (6X10)
Catalog number	0830908
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-126490B121
Generated	2026-08-05

Product Overview

Marker for terminal blocks

Marker for terminals, Strips, white, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: hook, for terminal width: 6.2 mm, useful surface: 6 x 10 mm, Number of individual indexes: 20

Marker for terminal blocks, Strip, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: latching, for terminal block width: 6.2 mm, Number of individual labels: 20, text field height: 10 mm, text field width: 6 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Terminal marking

Area of application Phoenix Contact

Pitch 6.2 mm

Type high

Data management status

Article revision 00

Marking

Number of individual labels 20

Number of individual labels per row 10

Number of marker strips 2

Identification technology UV LED technology

Dimensions Width 6 mm

Text field width 6.00 mm

Text field height 10.00 mm

Length 10 mm

Pitch 6.2 mm

Material specifications RoHS compliant yes

Color white

Material PC

Flammability rating according to UL 94 V2

Components free from silicone, halogen, and cadmium

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Wipe resistance of inscriptions

Specification IEC 61010-1:2010-06

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification DIN 50018:2013-05

Result Test passed

Climate level AHT 1.0 S

Cycles 2

Salt spray test

Specification DIN EN 60068-2-11:2000-02

Result Test passed

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 %

Standards and regulations Wipe resistance DIN EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-TM (6X10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.