


## INDUSTRIAL COMPONENT DATA

## UMK- C64M-VS 2970057 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-C64M-VS



|                 |                  |
|-----------------|------------------|
| Manufacturer    | PHOENIX CONTACT  |
| MPN / Reference | UMK-C64M-VS      |
| Catalog number  | 2970057          |
| Category        | Interface module |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-D8C63B9C9F    |
| Generated       | 2026-08-04       |

## Product Overview

Interface module

VARIOFACE module, for IEC 603/ DIN 41612 connectors, C construction, 64 poles, equipped in rows a, c, with male connector, screw-on cable housing

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

Key Commercial Data

Orderkey 2970057

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 230 (IF-2002)

GTIN 4017918087579

Weight per Piece (excluding packing) 298.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 135 mm

Height 77 mm

Depth 62.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

#### General

Max. perm. operating voltage 125 V

Max. perm. current (per branch) 1 A

Number of positions 64

Mounting position any

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IEC 603/DIN 41612 connection

Number of connections 1

Number of positions 64

#### Standards and Regulations

Standards/regulations DIN VDE 0110

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

#### Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss

7.027141152eCl@ss 8.027141152eCl@ss 9.027141152

ETIM 4.0EC002780ETIM 5.0EC002780ETIM 6.0E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-C64M-VS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.