

INDUSTRIAL COMPONENT DATA

UMSTBVK 2,5/ 5-STF-5,08BDNZ326 1775233 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMSTBVK 2,5/ 5-STF-5,08BDNZ326



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMSTBVK 2,5/ 5-STF-5,08BDNZ326
Catalog number	1775233
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-2DD5867CCF
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Rail connector, nominal section: 2.5 mm², rated current: 12 A, sizing voltage (III/2): 320 V, contact type: Connecting female, Number of potentials: 5, Number of rows: 1, Number of poles per row: 5, number of connections: 5, article family: UMSTBVK 2.5/.. -STF, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Rail, connection direction conductor/printed circuit board: 0 °, Stecksystem: CLASSIC COMBICON, Lock: Locking by screw, type of packaging: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1775233

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4046356492348

Weight per Piece (excluding packing) 17.880 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Pitch 5.08 mm

Dimension a 20.32 mm

General

Range of articles UMSTBVK 2,5/...-STF

Number of positions 5

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic slee...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMSTBVK 2,5/ 5-STF-5,08BDNZ326 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.