

INDUSTRIAL COMPONENT DATA

UCT2-TM 5/6 0829249 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT2-TM 5/6



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT2-TM 5/6
Catalog number	0829249
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-FF9BAECED2
Generated	2026-07-31

Product Overview

Marker for terminal blocks

UniCard materials for thermal transfer printer, for the labeling of Wago terminals, 72 units, labelable with THERMOMARK CARD and BLUEMARK LED, color: white

UniCard materials for thermal transfer printers, for labeling Wago terminal blocks, 72-section, can be labeled with THERMOMARK CARD and BLUEMARK LED, color: white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral Can be labeled via thermal transfer

Product propertiesProduct type Terminal marking

Area of application Wago: Terminal blocks

Pitch 5.2 mm

Type high

Data management status

Article revision 03

Marking

Number of individual labels 72

Number of individual labels per row 12

Identification technology Thermal transfer for sheets and cards, UV LED technology, direct laser marking

DimensionsWidth 4.35 mm
Text field width 4.20 mm
Height 2.65 mm
Text field height 8.40 mm
Length 10.2 mm
Pitch 5.2 mm
Material specificationsRoHS compliant yes
Color white (RAL 9010)
Material PC
Flammability rating according to UL 94 V0
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Components free from silicone and halogen
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Testing in a condensation changing climate in the presenc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT2-TM 5/6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.