

INDUSTRIAL COMPONENT DATA

US2-TM 100 0829268 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: US2-TM 100



Manufacturer	PHOENIX CONTACT
MPN / Reference	US2-TM 100
Catalog number	0829268
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-23AEE41C80
Generated	2026-07-29

Product Overview

Marker for terminal blocks

UniSheet markings for Wago terminals, labelable with THERMOMARK CARD, 12 units, color: white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0829268

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 175 (C-3-2017)

GTIN 4046356559591

Weight per Piece (excluding packing) 10.080 g

Custom tariff number 39204910

Country of origin DE (Germany)

Dimensions

Length (b) 10.9 mm

Width (a) 104 mm

Height (c) 0.5 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C

General

Color white

Type flat

Components Silicone-free

Flammability rating according to UL 94 V0

Material PVC

PVC

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 12

Number of individual labels per row 1

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type snap into tall marker groove

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V0

Classifications

eCl@ss 4.024190208eCl@ss 4.124190208eCl@ss 5.027149103eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss
7.027141137eCl@ss 8.027141137eCl@ss 9.027141137

ETIM 2.0EC000761ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC00076...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US2-TM 100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.