

INDUSTRIAL COMPONENT DATA

PSR-SCF-120UC/URM/2X21 2981376 PHOENIX CONTACT

Extension module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCF-120UC/URM/2X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCF-120UC/URM/2X21
Catalog number	2981376
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-B4DDBA42AB
Generated	2026-08-04

Product Overview

Extension module

Safe coupling relay with forced-conduction contacts, 2 switched contacts, 1 channel, fixed screw terminal, width: 17.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2981376

Packing unit 10 pc

Catalog page Page 279 (C-6-2017)

GTIN 4017918952907

Weight per Piece (excluding packing) 61.970 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Width 17.5 mm

Height 75 mm

Depth 60.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Input data

Nominal input voltage UN 120 V AC/DC

Input voltage range in reference to UN 0.85 ... 1.1

Typical input current at UN 9 mA

Typical response time 10 ms

Typical release time 10 ms

Output data

Contact type 2 PDT

Contact material AgNi

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 15 V AC/DC

Limiting continuous current 5 A (N/O contact)

3.5 A (N/C contact)

Maximum inrush current 6 A

Inrush current, minimum 10 mA

Interrupting rating (ohmic load) max. 144 W (24 V DC, ? = 0 ms)

288 W (48 V DC, ? = 0 ms)

88 W (110 V DC, ? = 0 ms)

110 W (220 V DC, ? = 0 ms)

1500 VA (250 V AC, ? = 0 ms)

Maximum interrupting rating (inductive load) on request

Switching capacity min. 0.24 W

Mechanical service life approx. 107cycles

Switching capacity (360/h cycles) 6 A (24 V DC; N/O contact)

3 A (230 V AC; N/O contact)

Output...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCF-120UC/URM/2X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.