

INDUSTRIAL COMPONENT DATA

PSR-SCF- 24UC/URM/2X21 2981363 PHOENIX CONTACT

Coupling relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCF-24UC/URM/2X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCF-24UC/URM/2X21
Catalog number	2981363
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-9BD5D5ACC5
Generated	2026-08-02

Product Overview

Coupling relay

Safe coupling relay with forced-conduction contacts, 2 switched contacts, 1 channel, fixed screw terminal, width: 17.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2981363

Packing unit 10 pc

Catalog page Page 279 (C-6-2017)

GTIN 4017918946906

Weight per Piece (excluding packing) 61.820 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Width 17.5 mm

Height 75 mm

Depth 60.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US 24 V AC/DC -15 % / +10 %

Rated control supply current IS typ. 30 mA

Power consumption at US typ. 0.72 W

Inrush current typ. 350 mA DC (?t s)

typ. 350 mA AC (?t = 2 ms at Us)

Typ. starting time with Us typ. 10 ms

Typical release time typ. 10 ms

Recovery time < 500 ms

Operating voltage display 1 x yellow LED

Maximum switching frequency 0.5 Hz

Filter time max. 1.5 ms (at S12; test pulse width)

7.5 ms (at S12; test pulse rate)

Test pulse rate = 5 x Test pulse width

Output data

Contact type 2 PDT

Contact material AgNi

Maximum switching voltage 230 V AC/DC (Observe the load curve)

Minimum switching voltage 5 V AC/DC

Limiting continuous current 5 A (N/O contact)

3.5 A (N/C contact)

Maximum inrush current 6 A

Inrush current, minimum 10 mA

Sq. Total current 50 A2

Interrupting rating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCF-24UC/URM/2X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.