

**INDUSTRIAL COMPONENT DATA**

# **UNO-PS/1AC/12DC/ 55W/H 1088850 PHOENIX CONTACT UNO POWER primary switch-mode power supply for DIN rail mount..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: UNO-PS/1AC/12DC/ 55W/H



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | PHOENIX CONTACT        |
| MPN / Reference | UNO-PS/1AC/12DC/ 55W/H |
| Catalog number  | 1088850                |
| Category        | DC-power supply        |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-1FC7E0191E          |
| Generated       | 2026-08-05             |

## **Product Overview**

UNO POWER primary switch-mode power supply for DIN rail mounting, IEC 60335-1, input: single-phase, output: 12 V DC/55 W

UNO POWER primary switched power supply for rail mounting, input: single-phase, output: 12 V DC/55 W

**STRUCTURED PRODUCT DATA**

## **Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

## **Classification & Catalog Path**

Catalog path **PHOENIX CONTACT > Power Supplies (PS)**

## **Additional Product Information**

ETIM for 1088850 Low-voltage industrial controls and switchgear (EC002540)

Feature Name

Feature Value

Voltage type (supply voltage) (EF002991)

AC

1st secondary output voltage (EF006792)

12 V

Max. output current 1 (EF008284)

4.6 A

Nominal value output voltage 1 (EF009393)

12 V

Nominal value output current 1 (EF009396)

4.6 A

Short-circuit-proof (EF007332)

Yes

Rated supply voltage AC 50 Hz (EF007076)

85 V

Rated supply voltage AC 60 Hz (EF007077)

100 V

Output voltage stabilized (EF003092)

Yes

Power consumption (EF000346)

127 VA

Power output (EF003034)

55 W

Stabilized (EF005302)

Yes

Type of electric connection (EF003961)

Screw connection

Suitable for rail mounting (EF003972)

Yes

Wall mounting possible (EF003973)

No

Modular version (EF001126)

No

Built-in height (EF000332)

90 mm

Direct mounting possible (EF005689)

No

Width (EF000008)

35 mm

Height (EF000040)

90 mm

Depth (EF000049)

84 mm

Suitable for safety functions (EF001597)

Yes

SIL according to IEC 61508 (EF009889)

None

Performance level according to EN ISO 13849-1 (EF007399)

None

Degree of protection (IP) (EF005474)

IP20

Degree of protection (NEMA) (EF011959)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UNO-PS/1AC/12DC/ 55W/H with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.