


INDUSTRIAL COMPONENT DATA

URTK/SP BN 0706061 PHOENIX CONTACT Test disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: URTK/SP BN



Manufacturer	PHOENIX CONTACT
MPN / Reference	URTK/SP BN
Catalog number	0706061
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-758ED5D161
Generated	2026-08-02

Product Overview

Test disconnect terminal block

Borne interrupts. for circ. Size, with sliding link, connection type: Screw connection, cross-section: 0.5 mm² - 10 mm², AWG: 20 - 10, width: 8.2 mm, mounting class: NS 35/7.5, NS 35/15, NS 32, color: brown

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 0706061

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918896041

Weight per Piece (excluding packing) 38.550 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 6 mm²

Color brown
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 50 A (with 10 mm² conductor cross section)
Nominal current I_N 41 A
Nominal voltage U_N 500 V
Open side panel No
Dimensions
Width 8.2 mm
Length 99.5 mm
Height NS 35/7,5 59 mm
Height NS 35/15 66.5 mm
Height NS 32 64 mm
Connection data
Note Terminal point
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 8
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross secti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / URTK/SP BN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.