

INDUSTRIAL COMPONENT DATA

US-WML 14 (25X19) CUS 1018765 PHOENIX CONTACT Cable marker label, Card, white, labeled, mounting type: adhes..

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WML 14 (25X19) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-WML 14 (25X19) CUS
Catalog number	1018765
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-31CE613980
Generated	2026-08-04

Product Overview

Cable marker label, Card, white, labeled, mounting type: adhesive, cable diameter: ≤ 14 mm, lettering field size: 25 x 19 mm, Number of individual labels: 8

Cable marker label, Card, white, labeled according to customer specifications, mounting class: glued, cable diameter range: 6.1 ... 14.2 mm, cable diameter: ≤ 14.2 mm, usable area: 25x19mm, Number of individual indexes: 8

Cable marker label, Card, white, labeled according to customer specifications, mounting type: adhesive, cable diameter range: 6.1 ... 14.2 mm, cable diameter: ≤ 14.2 mm, Number of individual labels: 8, text field height: 19 mm, text field width: 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker

Type Label

Data management status

Article revision 02

Marking

Number of individual labels 8

Number of individual labels per row 4

MountingMounting type adhesive

Material specificationsColor white (RAL 9010)

Material PVC

Base element material Vinyl film

Components Silicone-free

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 100 °C (121 °C) Test passed

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-01):2020-03

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Test passed

Ethanol (99 %)

[CAS No. 64-17-5] Test passed

Acetone (99 %)

[CAS No. 67-64-1] Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Test passed

Diesel

[CAS No. 68476-34-6] Test passed

IRM 901 T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WML 14 (25X19) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.