

INDUSTRIAL COMPONENT DATA

VS-FSDB-IP20SDA/981/2,0 SCO 1420171 PHOENIX CONTACT

Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-FSDB-IP20SDA/981/2,0 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-FSDB-IP20SDA/981/2,0 SCO
Catalog number	1420171
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-F2864D820B
Generated	2026-07-31

Product Overview

Patch cable

USB Cable-ready-made, shielded, black color, PVC outer sheath, USB Mini-B/IP 20 over USB Type-A/IP 20, length. 2 m
Assembled USB cable, shielded, color: black, PVC outer sheath, USB mini-B/IP20 on USB type A/IP20, length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataNotesTrade restriction

CE note The products are offered exclusively for export outside the EU and the European Economic Area.

Product propertiesProduct type Data cable preassembled

Application Standard

Number of positions 4

Shielded yes

Data management status

Article revision 06

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

Nominal current IN 1 A

Transmission medium Copper

Transmission characteristics (category) USB 2.0

Mechanical propertiesMechanical dataInsertion/withdrawal cycles ≥ 100

Material specificationsFlammability rating according to UL 94 V0

Connection dataPin assignment

Contact Color (signal designation) Contact (optional) 1 (M12 mini B) RD (+5 V) 1 (USB type A)

2 (M12 mini B) WH (DATA-) 2 (USB type A)

3 (M12 mini B) GN (DATA+) 3 (USB type A)

4 (M12 mini B) N.C.

5 (M12 mini B) BK (GND) 4 (USB type A)

ConnectorConnection 1

Type Plug straight USB type A / IP20

Degree of protection IP20

Connection 2

Type Socket straight M12 mini B / IP65

Material Cu alloy

Ni/Au

Degree of protection IP65

Cable/lineCable length 2 m

External sheath, color black

Ambient temperature (operation) -25 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditionsAmbient conditions

Degree of protection IP20 (USB type A)

IP65 (M12 mini B)

Ambient temperature (operation) -25 °C ... 80 °C (Cable, flexible installation)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-FSDB-IP20SDA/981/2,0 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.