


INDUSTRIAL COMPONENT DATA

USLKG 10-1 0442024 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 10-1



Manufacturer	PHOENIX CONTACT
MPN / Reference	USLKG 10-1
Catalog number	0442024
Category	Ground terminal block
Minimum order	1 Pcs
Document ID	EO-F90DA27D9A
Generated	2026-08-05

Product Overview

Ground modular terminal block

Ground terminal with screw connection, section: 0.5 ... 6 mm², AWG: 20 ... 8, width: 8.2 mm, colour: Yellow... green**STRUCTURED PRODUCT DATA**

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 0442024

Packing unit 50 pc

GTIN 4017918002244

Weight per Piece (excluding packing) 28.850 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of positions 1

Number of levels 1

Number of connections 2

Nominal cross section 10 mm²

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.82 W
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Dimensions
Width 8.2 mm
Length 42.5 mm
Height NS 35/7,5 47...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 10-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.