


**INDUSTRIAL COMPONENT DATA**

# USLKG 2,5 0441025 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 2,5



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | USLKG 2,5             |
| Catalog number  | 0441025               |
| Category        | Ground terminal block |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-1D4B50C5D4         |
| Generated       | 2026-08-05            |

## Product Overview

Ground modular terminal block

Terminal block, number of connections: 2, number of poles: 1, type of connection: Screw connection, cross-section: 0.2 mm² - 4 mm², type of fixing: PE foot with fixing screw, M3, mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0441025

Packing unit 50 pc

GTIN 4017918002138

Weight per Piece (excluding packing) 19.400 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of positions 1

Number of levels 1

Number of connections 2

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V2  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Open side panel No  
Terminal block mounting 0.6 Nm ... 0.8 Nm (PE foot with mounting screw, M3)  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg  
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3  
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3  
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3  
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3  
Dimensions  
Width 6.2 mm  
Length 42.5 mm  
Height NS 35/7,5 42 mm  
Height...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 2,5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.