


INDUSTRIAL COMPONENT DATA

USLKG 95 B 3048195 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 95 B



Manufacturer	PHOENIX CONTACT
MPN / Reference	USLKG 95 B
Catalog number	3048195
Category	Ground terminal block
Minimum order	10 Pcs
Document ID	EO-F6FDC20711
Generated	2026-08-05

Product Overview

Ground modular terminal block

Terminal block, Screws with internal hexagon, with slot for bridging, without fixing screw, number of connections: 2, number of poles: 1, connection type: Screw connection, Sizing section: 95 mm², cross-section: 25 mm² - 95 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3048195

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4017918939441

Weight per Piece (excluding packing) 312.750 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Screws with hexagonal socket

Number of positions 1

Number of levels 1

Number of connections 2
Nominal cross section 95 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 7.54 W
Open side panel No
Dimensions
Width 25 mm
Length 83 mm
Height NS 35/7,5 90.3 mm
Height NS 35/15 97.8 mm
Height NS 32 95.3 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-2
Conductor cross section solid min. 25 mm²
Conductor cross section solid max. 95 mm²
Conductor cross section AWG min. 4
Conductor cross section AWG max. 3/0
Conductor cross section flexible min. 25 mm²
Conductor cross section flexible max. 95 mm²
Min. AWG conductor cross section, flexible 4
Max. AWG conductor cross section, flexible 3/0
Conductor cross section flexible, with ferrule without plastic sleeve min. 35 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 95 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 35 mm²
Conductor cross section flexible, with fe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 95 B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.