


**INDUSTRIAL COMPONENT DATA**

# USLKG 95 B 3048195 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 95 B



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | USLKG 95 B            |
| Catalog number  | 3048195               |
| Category        | Ground terminal block |
| Minimum order   | 10 Pcs                |
| Document ID     | EO-F6FDC20711         |
| Generated       | 2026-08-06            |

## Product Overview

Ground modular terminal block

Terminal block, Screws with internal hexagon, with slot for bridging, without fixing screw, number of connections: 2, number of poles: 1, connection type: Screw connection, Sizing section: 95 mm<sup>2</sup>, cross-section: 25 mm<sup>2</sup> - 95 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3048195

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4017918939441

Weight per Piece (excluding packing) 312.750 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Screws with hexagonal socket

Number of positions 1

Number of levels 1

Number of connections 2  
Nominal cross section 95 mm<sup>2</sup>  
Color green-yellow  
Insulating material PA  
Flammability rating according to UL 94 V2  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 7.54 W  
Open side panel No  
Dimensions  
Width 25 mm  
Length 83 mm  
Height NS 35/7,5 90.3 mm  
Height NS 35/15 97.8 mm  
Height NS 32 95.3 mm  
Connection data  
Note Please observe the current carrying capacity of the DIN rails.  
Connection method Screw connection  
Connection in acc. with standard IEC 60947-7-2  
Conductor cross section solid min. 25 mm<sup>2</sup>  
Conductor cross section solid max. 95 mm<sup>2</sup>  
Conductor cross section AWG min. 4  
Conductor cross section AWG max. 3/0  
Conductor cross section flexible min. 25 mm<sup>2</sup>  
Conductor cross section flexible max. 95 mm<sup>2</sup>  
Min. AWG conductor cross section, flexible 4  
Max. AWG conductor cross section, flexible 3/0  
Conductor cross section flexible, with ferrule without plastic sleeve min. 35 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 95 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 35 mm<sup>2</sup>  
Conductor cross section flexible, with fe...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 95 B with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.