

INDUSTRIAL COMPONENT DATA

UT 35-PE/S 3215928 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 35-PE/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 35-PE/S
Catalog number	3215928
Category	Ground terminal block
Minimum order	1 Pcs
Document ID	EO-E228DB987F
Generated	2026-08-05

Product Overview

Ground modular terminal block

Terminal block, With threaded foot, number of connections: 2, connection type: Screw connection, Sizing section: 35 mm², cross-section: 1.5 mm² - 35 mm², fixing type: PE foot with fixing screw, M5, mounting class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3215928

Packing unit 50 pc

Catalog page Page 255 (C-1-2017)

GTIN 4046356595810

Weight per Piece (excluding packing) 73.690 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Nominal cross section 35 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Open side panel No
Terminal block mounting 2.5 Nm ... 3 Nm (PE foot with mounting screw, M5)
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 1.857 (m/s²)²/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Dimensions
Width 16 mm
End cover width 2.2 mm
Length 60.2 mm
Height NS 35/7,5 65.7 mm
Height NS 35/15 73.2 mm
Connection data
Note Pleas...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 35-PE/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.