

INDUSTRIAL COMPONENT DATA

UT 4-MT-P/P-EX BU 1291258 PHOENIX CONTACT Blade interruptible terminal block, nominal voltage: 500 V, nomina..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-MT-P/P-EX BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-MT-P/P-EX BU
Catalog number	1291258
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-593C201C06
Generated	2026-08-04

Product Overview

Blade interruptible terminal block, nominal voltage: 500 V, nominal current: 20 A, connection type: Screw connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, colour: blue Interruptible terminal per blade, rated voltage: 500 V, rated current: 20 A, connection type: Screw connection, Sizing section: 2.5 mm², section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

ETIM for 1291258 Terminal blocks (EC000902)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Rated current I_n (EF008250)

20 A
Rated voltage (EF000228)
500 V
Type of electrical connection 1 (EF002526)
Screw connection
Type of electrical connection 2 (EF002527)
Screw connection
Number of clamp positions per level (EF002660)
2
Internally connected stages (EF002661)
Yes
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
6.2 mm
Height (EF000040)
57.8 mm
Depth (EF000049)
49.1 mm
Closing plate required (EF002525)
No
Colour (EF000007)
Blue
Type of cross disconnection (EF002546)
None
With integrated test socket (EF002547)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-MT-P/P-EX BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.