

INDUSTRIAL COMPONENT DATA

UT 4-MTL-P/P KNIFE-WH 3046150 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-MTL-P/P KNIFE-WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-MTL-P/P KNIFE-WH
Catalog number	3046150
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-3B9A44B744
Generated	2026-08-05

Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, with drive tab, white disconnect blade and threaded sockets for test sockets to house test pins, nominal voltage: 500 V, nominal current: 20 A, connection type: Screw connection, Sizing section: 2.5 mm², section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3046150

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 236 (C-1-2017)

GTIN 4055626063287

Weight per Piece (excluding packing) 13.990 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Maximum load current 20 A (with 6 mm² conductor cross section)
Nominal current I_N 20 A
Nominal voltage U_N 500 V
Open side panel No
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
4 mm² / 0.9 kg
6 mm² / 1.4 kg
Tensile test result Test passed
Conductor cross section tensile test 0.14 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-MTL-P/P KNIFE-WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.