

INDUSTRIAL COMPONENT DATA

UT 6 WH 3045198 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 6 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 6 WH
Catalog number	3045198
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-6B37B9941C
Generated	2026-08-05

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 1000 V, nominal current: 41 A, number of connections: 2, connection type: Screw connection, Sizing cross-section: 6 mm², cross-section: 0.2 mm² - 10 mm², mounting class: NS 35/7.5, NS 35/15, color: white

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3045198

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918975531

Weight per Piece (excluding packing) 13.820 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 6 mm²

Color white

Insulating material PA

Flammability rating according to UL 94 V0

Area of application Railway industry

Machine building

Plant engineering

Process industry

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.31 W

Maximum load current 57 A (with 10 mm² conductor cross section)

Nominal current I_N 41 A

Nominal voltage U_N 1000 V

Open side panel Yes

Dimensions

Width 8.2 mm

End cover width 2.2 mm

Length 47.7 mm

Height NS 35/7,5 47.5 mm

Height NS 35/15 55 mm

Connection data

Connection method Screw connection

Connection in acc. with standard IEC 60947-7-1

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 10 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 8

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 10 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 8

Conductor cross section flexible, with ferrule without plastic sle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 6 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.