


INDUSTRIAL COMPONENT DATA

UTI 6-L/N 3076045 PHOENIX CONTACT Installation level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 6-L/N



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTI 6-L/N
Catalog number	3076045
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-A9E45037BC
Generated	2026-08-01

Product Overview

Installation level terminal block

Distribution floor terminal block, nominal voltage: 400 V, nominal current: 38 A, Screw connection, Dimensioning cross-section: 6 mm², cross-section: 0.2 mm² - 10 mm², installation class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3076045

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4046356817660

Weight per Piece (excluding packing) 27.740 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Assembly instruction:

In order to securely fix the neutral busbar in place, support brackets must be placed at the beginning and end of each terminal strip as well as every 20 cm on longer terminal strips.

The corresponding support brackets can be found at phoenixcontact.net/products

Number of levels 3
Number of connections 4
Nominal cross section 6 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W (the value is multiplied when connecting multiple levels)
Ambient temperature (operation) -40 °C ... 130 °C
Nominal current I_N 38 A (with 6 mm² conductor cross section)
Maximum load current 47 A (with 10 mm² conductor cross section)
Nominal voltage U_N 400 V
250 V (phase conductor/N)
Open side panel Yes
Dimensions
Width 8.2 mm
Length 95 mm
Height NS 35/7,5 51.5 mm
Height NS 35/15 59 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 10 mm²
Conductor cross section AWG min. 24
Condu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 6-L/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.