


**INDUSTRIAL COMPONENT DATA**

# UTT 2,5-2R/NAMUR 3046671 PHOENIX CONTACT

## Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 2,5-2R/NAMUR



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | UTT 2,5-2R/NAMUR         |
| Catalog number  | 3046671                  |
| Category        | Component terminal block |
| Minimum order   | 50 Pcs                   |
| Document ID     | EO-10E5E9499C            |
| Generated       | 2026-08-05               |

### Product Overview

Component terminal block

Terminal block for components, connection type: Screw connection, Sizing cross-section: 2.5 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7.5, NS 35/15, colour: grey

Component terminal block, connection method: Screw connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7.5, NS 35/15, color: gray

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

### Additional Product Information

Technical dataProduct propertiesProduct type Component terminal block

Number of connections 4

Number of rows 2

Potentials 2

Data management status

Article revision 05

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated insulation voltage 500 V

Rated surge voltage 6 kV

Connection data Number of connections per level 2  
Nominal cross section 2.5 mm<sup>2</sup>  
Level 1+2  
Screw thread M3  
Tightening torque 0.5 ... 0.6 Nm  
Stripping length 9 mm  
Internal cylindrical gage A3  
Conductor cross section rigid 0.14 mm<sup>2</sup> ... 4 mm<sup>2</sup>  
Cross section AWG 26 ... 12 (converted acc. to IEC)  
Conductor cross section flexible 0.14 mm<sup>2</sup> ... 4 mm<sup>2</sup>  
Conductor cross section, flexible [AWG] 26 ... 12 (converted acc. to IEC)  
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
2 conductors with same cross section, solid 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
2 conductors with same cross section, flexible 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Nominal cross section 2.5 mm<sup>2</sup>  
Component type Resistance  
Resistance value 10 k?  
Tolerance 1 %  
Electric strength 350 V  
Component type Resistance  
Resistance value 1 k?  
Tolerance 1 %  
Electric strength 350 V  
Dimensions Width 5.2 mm  
End cover width 2.2...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 2,5-2R/NAMUR with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.