


**INDUSTRIAL COMPONENT DATA**

# UTT 4-L/N 3044788 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTT 4-L/N



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | UTT 4-L/N                   |
| Catalog number  | 3044788                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-4151143778               |
| Generated       | 2026-08-05                  |

## Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 30 A, connection type: Screw connection, Dimensioning cross-section: 4 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, installation class: NS 35/7.5, NS 35/15, colour: grey

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

## Additional Product Information

Key Commercial Data

Orderkey 3044788

Packing unit 50 pc

GTIN 4017918997113

Weight per Piece (excluding packing) 20.040 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

Nominal cross section 4 mm<sup>2</sup>

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)

Connection in acc. with standard IEC 60947-7-1

Nominal current IN 30 A

Maximum load current 36 A (with 6 mm<sup>2</sup> conductor cross section)

Nominal voltage UN 800 V

Open side panel Yes

Relative insulation material temperature index (Elec.; UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Dimensions

Width 6.2 mm

Le...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 4-L/N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.