

INDUSTRIAL COMPONENT DATA

UTTB 4 WH 1237651 PHOENIX CONTACT Double-level terminal block, nominal voltage: 800 V, nominal current: 30 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 4 WH



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTTB 4 WH
Catalog number	1237651
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-499120AD97
Generated	2026-07-31

Product Overview

Double-level terminal block, nominal voltage: 800 V, nominal current: 30 A, connection type: Screw connection, 1st and 2nd floor, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: white
Double-decker terminal, connection type: Screw connection, section: 0.14 mm² - 6 mm², AWG: 26 - 10, width: 6.2 mm, color: white, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

ETIM for 1237651 Terminal blocks (EC000897)

Feature Name

Feature Value

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.14 mm²

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Rated current I_n (EF008250)

30 A
Rated voltage (EF000228)
800 V
Type of electrical connection 1 (EF002526)
Screw connection
Type of electrical connection 2 (EF002527)
Screw connection
Number of levels (EF002659)
2
Number of clamp positions per level (EF002660)
2
Suitable for conductor material (EF012572)
Aluminium/copper
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Width (EF000008)
6.2 mm
Height (EF000040)
69.9 mm
Depth (EF000049)
65 mm
Explosion-tested version 'Ex e' (EF008498)
Yes
Closing plate required (EF002525)
Yes
Colour (EF000007)
White
Internally connected stages (EF002661)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 4 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.