

INDUSTRIAL COMPONENT DATA

UW 25-POT BK 1036567 PHOENIX CONTACT Panel feed-through terminal block, number of positions: 1

Brand: PHOENIX CONTACT | Manufacturer Part Number: UW 25-POT BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	UW 25-POT BK
Catalog number	1036567
Category	Panel feed-through terminal block
Minimum order	25 Pcs
Document ID	EO-BCB7C07866
Generated	2026-08-05

Product Overview

Panel feed-through terminal block, number of positions: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1036567

Packing unit 1

GTIN 4055626560441

Custom tariff number 85369010

Item properties

Connection capacity, external

Material data - contact

Dimensions for the product

General product information

Air clearances and creepage distances

Environmental Product Compliance

Electrical parameters

Connection capacity, internal

Material data - housing

Packaging information

Electrical tests

Standards and Regulations

Classifications

Item properties

Brief article description Panel feed-through terminal block

Range of articles UW 25-POT

Pitch 15.1 mm

Number of positions 1

Connection method Screw connection with tension sleeve

Number of connections 2

Number of potentials 1

Back to topElectrical parameters

Nom. voltage 630 V

Back to topConnection capacity, external

Connection method Screw connection with tension sleeve

Connection direction of the conductor to plug-in direction 0 °

Conductor cross section solid 6 mm² ... 35 mm²

Conductor cross section flexible 10 mm² ... 25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve 4 mm² ... 25 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 4 mm² ... 25 mm²

2 conductors with same cross section, solid 2.5 mm² ... 10 mm²

2 conductors with same cross section, flexible 4 mm² ... 10 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 2.5 mm² ... 10 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 2.5 mm²...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UW 25-POT BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.