

INDUSTRIAL COMPONENT DATA

UWV 95/S 1713226 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UWV 95/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	UWV 95/S
Catalog number	1713226
Category	Panel feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-374B14F155
Generated	2026-08-05

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Screw connection with traction capsule, number of poles: 1, charging current: 232 A, conductor connection direction with respect to the plug direction: -90 °, width: 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1713226

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626308395

Weight per Piece (excluding packing) 197.280 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of connections 2

Nominal cross section 95 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Insulating material group I

Ambient temperature (operation) -40 °C (Depending on the current carrying capacity/derating curve)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 232 A

Maximum load current 232 A

Nominal voltage U_N 1000 V

Number of positions 1

Dimensions

Width 25 mm

Pitch 25 mm

Plate thickness 1 mm ... 5 mm

Connection data

Connection side outside

Connection method Screw connection

Conductor cross section solid min. 25 mm²

Conductor cross section solid max. 95 mm²

Conductor cross section flexible min. 35 mm²

Conductor cross section flexible max. 95 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 95 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 95 mm²

2 conductors with same cross section, solid min. 16 mm²

2 conductors with same cross section, solid m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UWV 95/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.